

DOE/BPA DG Workshops for Code Officials

IdaTech, LLC Bend, OR, USA www.idatech.com

Warren Ewing (541) 322-1051 wewing@idatech.com



- Introduction of IdaTech
- Product Introduction
- Fuel Cell System Overview
- Integrated Safety Devices
- Identified Codes and Standards Referenced in IdaTech Designs
- Third Party Evaluation
- Conclusion



IdaTech Overview

- Founded in 1996 as Northwest Power Systems
- Currently employs 75 Employees
- IDACORP, Inc. (NYSE: IDA) purchased majority share in 1999
- Core competencies are fuel processing technology, fuel cell system integration & controls
- Intellectual Property: 13 Patents, >50 in Process
- More than 25 systems operating in Japan, Europe, and North America (1 & 5kW)
- Commercialized Fuel Processor Module (FPM-20)
- Developed and Tested PV/FC Hybrid Solution
- IdaTech's Functional Organization
 - Engineering & Advanced R&D
 - Operations Manufacturing & Service
 - Finance & Administration
 - Marketing & Sales
 - Business Development & Government Programs



Mt. Bachelor from Todd Lake



- Introduction
- Product Introduction
- Fuel Cell System Overview
- Integrated Safety Devices
- Identified Codes and Standards Referenced in IdaTech Designs
- Third Party Evaluation
- Conclusion



IdaTech Products



FPM 20™ Fuel Processor Module

Part of IdaTech's family of fuel

processors

*** Commercially Available ***



FCS 1200™ Fuel Cell System
Field Test Available
Targeted Availability Early
2003



FCS 5000™ Fuel Cell System Undergoing field-testing



FPM 20™ Fuel Processor Module



Entry level fuel processor powers 2 kW fuel cell

Specifications

- Fully packaged subsystem
- Production rate >30 slm (rated at 20 slm)
- Fuel consumption 2.0 L/hr (0.53 Gallons/hr)
- >99.9% H₂ with <1 ppm CO, < 3 ppm CO₂
- Exhaust: Flow=22 L/sec, Temp=77C max (46 cfm, 170F)
- Quiet operation <50 db at 1 m (39 in.)
- 31 x 37 x 47 cm (12 x 14 x 18 in.); 36 kg (70 lbs)
- RS-485 communication interface
- Operates on methanol/de-ionized water mix



FCS 1200™ Fuel Cell System



Specifications

- Rated 1.2 kW, 1 kW continuous output
- Fuel consumption 1.3 L/hr (0.35 Gallons/hr) operates for 8 hours using standard fuel tank
- Exhaust: Flow=71 L/sec, Temp=60C max (150 cfm, 140F)
- Mass 100 kg (220 lbs.)
- Dimensions 81 x 60 x 50 cm (32 x 24 x 20 in)
 - Load following
 - Grid-Independent/Grid-Connected/PV-Connected
 - 1.0 kWe net continuous
 - 1.5 kWe peaking (w/battery)
 - $\eta_e = 0.29$
 - 200 watt parasitic
 - Ballard NexaTM Fuel Cell
 - Remote monitoring
 - Remote Start/Stop



FCS 5000™ Fuel Cell System



Specifications

- 5 kW fully integrated CHP Fuel Cell System
- Rated 5 kW, 3.4 kW continuous output
- Fuel consumption 2.2 L/hr (0.58 Gallons/hr)
- Exhaust: Flow=57 L/sec, Temp=70C max (120 cfm, 160F)
- Mass: 304 kg (670 lbs.)
- Dimensions: 92 x 67 x 155 cm (36 x 27 x 61 in.)
 - Load following
 - Grid-Independent/Grid-Connected
 - 3.0 kWe continuous
 - 10.0 kWe peaking (w/batteries)
 - 1.2 kWt (cathode only)
 - $\eta_e = 0.36$
 - $\eta_{CHP} = 0.45$
 - 250 watt parasitic
 - UTC Fuel Cell
 - Modular architecture
 - Remote monitoring




- Introduction
- Product Introduction
- Fuel Cell System Overview
- Integrated Safety Devices
- Identified Codes and Standards Referenced in IdaTech Designs
- Third Party Evaluation
- Conclusion




PEM Fuel Cell System (FCS)


- Inputs
 - Fuel: Hydrocarbons or Alcohols
 - Ambient Air
- Outputs
 - Exhaust: Water Vapor and Carbon Dioxide
 - Power: Grid Independent or Grid-Connected






Fuel Processor








Fuel Cell Module



- Electrochemical Process
- Direct Conversion to Electricity
- $2H_2 + O_2 \longrightarrow 2H_2O + Electricity + Heat$
- Continuous as long as Air (O₂) & H₂ are provided





Fuel Cell Technology





Power Conditioning Module







- Introduction
- Product Introduction
- Fuel Cell System Overview
- Integrated Safety Devices
- Identified Codes and Standards Referenced in IdaTech Designs
- Third Party Evaluation
- Conclusion



Safety Devices

- Breakers and Fuses
- Fuel Leak Detection
- Internal Hydrogen Sensor
- Cabinet Temperature Sensor
- Intrinsically Safe Ventilation System
- Carbon Monoxide Detector/Alarm
- Combustible Gas Detector/Alarm
- Emergency Stop Button



Safety Devices (continued)

- Redundant, Normally Closed UL Listed Valves for the Fuel Supply
- Redundant, Manually Operated Fuel Shut-Off Valves
- Software Safety Devices
 - Pressure
 - Temperature
 - Humidity
 - Current
 - Voltage
 - Air Flow
 - "Event" Timers
 - CPU "Watch Dog"




- Introduction
- Product Introduction
- Fuel Cell System Overview
- Integrated Safety Devices
- Identified Codes and Standards
 Referenced in IdaTech Designs
- Third Party Evaluation
- Conclusion



Interfaces

Stationary Fuel Cell System





Product Standards

Used to Certify Equipment

- ANSI Z21.83 Standard on Fuel Cell Power Plants.
 Scope includes stationary FCS. Currently addresses natural gas and propane fueled systems.
- ANSI CSA FC 1 This proposed standard will replace Z21.83 and be broadened to include most types of fuels, gas and liquid, hydrocarbons and alcohols.
- ANSI CSA FC 3 Draft Portable Fuel Cell Power Generators. Scope includes portable FCS.



Installation Standards

Used to Install Equipment

- NFPA 70 National Electrical Code, Article 692
- NFPA 54 National Fuel Gas Code
- NFPA 58 Liquefied Petroleum Gas Code
- NFPA 31 Installation of Oil-Burning Equipment
- NFPA 853 Installation of Stationary Fuel Cell Power Plants. The scope of this standard is for FCS exceeding 50 kW. Work is in progress to revise this standard to include all Stationary Systems (removes the 50 kW clause). Available for public comment through October 4, 2002.



Interconnection Standards

Grid-Connect and Grid Independent

- UL 1741 Standard for Inverters, Converters, and Controllers for use in Independent Power Systems.
 Scope includes both Grid-Tied and Grid Independent systems.
- IEEE P 1547 Standard for Interconnecting
 Distributed Resources with Electric Power Systems.
 Scope establishes criteria for interconnection of
 Distributed Resources with Electric Power Systems
- In the future these two standards will be harmonized, however IEEE P1547 is still a work in progress. At some point the work done in P1547 will be adopted into UL 1741.



- Introduction
- Product Introduction
- Fuel Cell System Overview
- Integrated Safety Devices
- Identified Codes and Standards Referenced in IdaTech Designs
- Third Party Evaluation
- Conclusion



Field Evaluations

A successful "Field Investigation" performed on IdaTech's FCS-5000 used the following Standards:

- UL 2262 Outline of Investigation on PEM type Fuel Cell Power Plants. This is an internal (UL) document developed to help the NRTL assess PEM fuel cells. It is not a national standard and will go away once the proper national standards are developed that cover this topic.
- ANSI Z21.83
- NFPA 70



Field Evaluations (continued)

Focused on the National Electrical Code - 2002 Edition

- Grounding-Article 250
- Guarding of Live Parts-Article 110-27
- Overcurrent Protection-Article 240
- Wiring Ampacity-Article 310
- Wiring Methods-Article 300



- Introduction
- Product Introduction
- Fuel Cell System Overview
- Integrated Safety Devices
- Identified Codes and Standards Referenced in IdaTech Designs
- Third Party Evaluation
- Conclusion



Conclusions:

Fuel Cell Technologies:

- Fuel cell technology is progressing down a path toward commercialization...most near-term sited units will be for demonstration purposes.
- Collaboration needs to accelerate between code officials and industry in order to properly prepare for the future of fuel cell technology.
- The industry and manufacturers need continual feedback and input from federal, state, and local agencies.
- Overview of the FCS 1200 fuel cell system on display today.